



S.R.S SYNTEX LIMITED

Regd. Office: 40- 41 Om Textile Tower, Pur Road Bhilwara 311001
Email: Info@srsduratech.com
Phone No. : 9166691899, 01482 243098

PVC COATED FABRIC

SRS 270 GSM BSC

UV RESISTANT
FINISH: TURBO MATT
TYPE OF YARN : HIGH TENACITY LOW SHRINKAGE POLYSTER YARN
WEAVE:PLAIN
DENIER : 500D
FIRE RETARDANCY : NFR

PROPERTIES		UNIT	TEST METHOD	SPECIFICATION
Weight		GSM	IS 7016 PART I 1982	270
Thickness		MM	IS 7016 PART I 1981	0.25
Breaking Strength	Warp	KG/5CM	IS 7016 PART II 1981	160
	Weft	KG/5CM	IS 7016 PART II 1981	150
Tear Strength	Warp	N	IS 7016 PART III 1981	15
	Weft	N	IS 7016 PART III 1981	15
Adhesion Strength		KG/5CM	IS 7016 PART V 1987	4
Water Proofness			IS 7016 PART VII 1986	No leak

AVAILABLE UP TO **3.2M** SEAMLESS / **STANDARD 50M ROLL LENGTH**

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. SRS Duratech reserves the right to change/modify the data without prior notice.