



# S.R.S SYNTEX LIMITED

Regd. Office: 40- 41 Om Textile Tower, Pur Road Bhilwara 311001  
Email: Info@srsduratech.com  
Phone No. : 9166691899, 01482 243098

## PVC COATED FABRIC

### SRS 430 GSM BSC

UV RESISTANT  
FINISH: TURBO MATT / GLOSS  
TYPE OF YARN : HIGH TENACITY LOW SHRINKAGE POLYSTER YARN  
WEAVE:PLAIN  
DENIER : 1000D  
FIRE RETARDANCY : NFR

PROPERTIES		UNIT	TEST METHOD	SPECIFICATION
Weight		GSM	IS 7016 PART I 1982	430
Thickness		MM	IS 7016 PART I 1982	0.38
Breaking Strength	Warp	KG/5CM	IS 7016 PART II - 1981	210
	Weft	KG/5CM	IS 7016 PART II - 1981	210
Tear Strength	Warp	N	IS 7016 PART III 1981	35
	Weft	N	IS 7016 PART III 1981	35
Adhesion Strength		KG/5CM	IS 7016 PART V 1987	4
Water Proofness		ML	IS 7016 PART VII 1987	No leak

AVAILABLE UP TO **3.2M** SEAMLESS / **STANDARD 50M ROLL LENGTH**

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. SRS Duratech reserves the right to change/modify the data without prior notice.