



S.R.S SYNTEX LIMITED

Regd. Office: 40- 41 Om Textile Tower, Pur Road Bhilwara 311001
Email: Info@srsduratech.com
Phone No. : 9166691899, 01482 243098

PVC COATED FABRIC

SRS 900 GSM BSC

UV RESISTANT
FINISH: TURBO MATT / GLOSS/ LACQUER
TYPE OF YARN: HIGH TENACITY LOW SHRINKAGE POLYSTER YARN
WEAVE: PLAIN
DENIER : 1000D
FIRE RETARDANCY : NFR

PROPERTIES		UNIT	TEST METHOD	SPECIFICATION
Weight		GSM	IS 7016 PART I	900
Thickness		MM	IS 7016 PART I	0.70
Tensile Strength	Warp	KG/5CM	IS 7016 PART II	250
	Weft	KG/5CM	IS 7016 PART II	230
Tear Strength	Warp	KG	IS 7016 PART III	35
	Weft	KG	IS 7016 PART III	30
Adhesion Strength		KG/5CM	IS 7016 PART V	8
Water Proofness		ML	IS 7016 PART VII	No leak

AVAILABLE UP TO **3.2M** SEAMLESS / **STANDARD 50M ROLL LENGTH**

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. SRS Duratech reserves the right to change/modify the data without prior notice.