



S.R.S SYNTEX LIMITED

Regd. Office: 40- 41 Om Textile Tower, Pur Road Bhilwara 311001

Email: Info@srsduratech.com

Phone No. : 9166691899, 01482 243098

PVC COATED FABRIC

SRS 430 GSM BSC

UV RESISTANT

FINISH: TURBO MATT / GLOSS

TYPE OF YARN : HIGH TENACITY LOW SHRINKAGE POLYESTER YARN

WEAVE:PLAIN

DENIER : 1000D

FIRE RETARDANCY : NFR

PROPERTIES		UNIT	TEST METHOD	SPECIFICATION
Weight		GSM	IS 7016 PART I 1982	430
Thickness		MM	IS 7016 PART I 1982	0.38
Breaking Strength	Warp	KG/5CM	IS 7016 PART II - 1981	210
	Weft	KG/5CM	IS 7016 PART II - 1981	210
Tear Strength	Warp	N	IS 7016 PART III 1981	35
	Weft	N	IS 7016 PART III 1981	35
Adhesion Strength		KG/5CM	IS 7016 PART V 1987	4
Water Proofness		ML	IS 7016 PART VII 1987	No leak

AVAILABLE UP TO **3.2M** SEAMLESS / **STANDARD 50M ROLL LENGTH**

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. SRS Duratech reserves the right to change/modify the data without prior notice.