



S.R.S SYNTEX LIMITED

Regd. Office: 40- 41 Om Textile Tower, Pur Road Bhilwara 311001

Email: Info@srsduratech.com

Phone No. : 9166691899, 01482 243098

PVC COATED FABRIC - ONE SIDED COATED

SRS 700 GSM SSC

UV RESISTANT

FINISH: MATT

TYPE OF YARN : MADE FROM HIGH TENACITY POLYESTER FILAMENT YARN

WEAVE:PLAIN

FIRE RETARDANCY : NFR

PROPERTIES		UNIT	TEST METHOD	SPECIFICATION	CF/27LN0015
Product Weight		GSM	IS 7016 PART I - 2019	700	704
Breaking Strength	Warp Weft	KG/ 5CM	IS 7016 PART II - 2022	260 260	303 290
Tear Strength	Warp Weft	KG	IS 7016 PART III 2022	45 40	51.7 46.2
Adhesion Strength		KG/5CM	IS 7016 PART V	7	8.42
Water Proofness @ 220 PSI		-	IS 7016 PART VII -1986	NO LEAK	Pass

AVAILABLE UP TO **3.2M** SEAMLESS / **STANDARD 50M ROLL LENGTH**

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. SRS Duratech reserves the right to change/modify the data without prior notice.