



# S.R.S SYNTEX LIMITED

Regd. Office: 40- 41 Om Textile Tower, Pur Road Bhilwara 311001

Email: Info@srsduratech.com

Phone No. : 9166691899, 01482 243098

## PVC COATED FABRIC

### SRS 760 GSM BSC

UV RESISTANT

FINISH: MATT / GLOSS

TYPE OF YARN: HIGH TENACITY LOW SHRINKAGE POLYESTER YARN

WEAVE: PLAIN

DENIER : 1000D

FIRE RETARDANCY : NFR

| PROPERTIES        |      | UNIT   | TEST METHOD           | SPECIFICATION |
|-------------------|------|--------|-----------------------|---------------|
| Product Weight    |      | GSM    | IS 7016 PART I 1982   | 760           |
| Thickness         |      | MM     | IS 7016 PART I 1982   | 0.55          |
| Breaking Strength | Warp | KG/5CM | IS 7016 PART II 1981  | 230           |
|                   | Weft | KG/5CM | IS 7016 PART II 1981  | 220           |
| Tear Strength     | Warp | KG     | IS 7016 PART III 1981 | 35            |
|                   | Weft | KG     | IS 7016 PART III 1981 | 30            |
| Adhesion Strength |      | KG/5CM | IS 7016 PART V 1987   | 7             |
| Water Proofness   |      | -      | IS 7016 PART VII 1987 | No leak       |

AVAILABLE UP TO **3.2M** SEAMLESS / **STANDARD 50M ROLL LENGTH**

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. SRS Duratech reserves the right to change/modify the data without prior notice.