



S.R.S SYNTEX LIMITED

Regd. Office: 40- 41 Om Textile Tower, Pur Road Bhilwara 311001

Email: Info@srsduratech.com

Phone No. : 9166691899, 01482 243098

PVC COATED FABRIC

SRS 900 GSM BSC

UV RESISTANT

FINISH: TURBO MATT / GLOSS/ LACQUER

TYPE OF YARN: HIGH TENACITY LOW SHRINKAGE POLYESTER YARN

WEAVE: PLAIN

DENIER : 1000D

FIRE RETARDANCY : NFR

| PROPERTIES | | UNIT | TEST METHOD | SPECIFICATION |
|-------------------|------|--------|------------------|---------------|
| Weight | | GSM | IS 7016 PART I | 900 |
| Thickness | | MM | IS 7016 PART I | 0.70 |
| Tensile Strength | Warp | KG/5CM | IS 7016 PART II | 250 |
| | Weft | KG/5CM | IS 7016 PART II | 230 |
| Tear Strength | Warp | KG | IS 7016 PART III | 35 |
| | Weft | KG | IS 7016 PART III | 30 |
| Adhesion Strength | | KG/5CM | IS 7016 PART V | 8 |
| Water Proofness | | ML | IS 7016 PART VII | No leak |

AVAILABLE UP TO **3.2M** SEAMLESS / **STANDARD 50M ROLL LENGTH**

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. SRS Duratech reserves the right to change/modify the data without prior notice.